


MOUNTING HOLE PRINT : 98 X 65

SPECIFICATIONS (Ta=32°C)	CODE #	DESCRIPTION
Heat Transfer Cold side	A	Air
Heat Transfer Warm side	A	Air
Cascade	-	
Cooling Effect	032	32 W at dT=0°C and Ta=32°C
Voltage Nominal	12	12 VDC (14,7 VDC MAX)
Current Nominal TE-Module(s)		4,9 A at dT=0°C PE-127-14-15-S
Fan(s) Cold side	2	12VDC, 0,23A, 60x60x25, MTBF 40.000 hrs L10
Fan(s) Warm side	2	12VDC, 0,23A, 60x60x25, MTBF 40.000 hrs L10
Thermostat / Regulation & Sensor	0	None
Thermostat Settings Trimmable Accuracy & Hysteresis	0	None
Thermostat Position & Casing	0	None (Connections PC board on warm side heat sink)
Options: Protections Rapid Cooling / Economy	0	None None
Weight Overheating Thermostat Max. operating Temperature Enclosed Packing		1,4 kg net None 50°C ambient Mounting Screws(4X) Individual paper box

POS	ITEM No.:	DESCRIPTION	QTY	NOTE
1	Cover	Alu, anodised black	2	removable on cold side
2	Heat sink	Alu, anodised black	2	
3	Fan&Finger guard	Plastics&Chromated steel	2+2	
4	Seal	Polyethylene	1	no CFC
5	Connector	± Input terminal(screws) on PC board	1	TEM & Fans

Qty/Product:		Material:		Project:	
Designed by: Pavel Cech	Approved by / sign: Hans Lindberg	Customer:	Date/Rev.No: S-99-05-31	Scale: 1	COOLING-ASSEMBLY
 Supercool AB Box 27, 40120 Göteborg, Sweden tel:+46 31 420530, fax:+46 31 247909 e-mail: pavel@supercool.se www.supercool.se		AA-032-12-22-00-00	SS-IS02768-1	Sheet 1/1	